

SUNSCREENS

EXTRAVIEW® PLUS SUNSCREENS

Applications

Roller Blinds
Roman Shades
Panel Glide

Composition

PVC Coated Fibreglass

Weight

400gsm ± 10

Fabric Thickness

0.50mm

Roll Width

2.5m
3.0m (selected colours)

Openness Factor

6% average

Colour Fastness

6-7 Blue Scale

Stiffness

40mm ± 5mm

20 Colours Available


Woven in Australia

Low VOCs


MULTIVISION® Concept




Midnight




Midnight Smudge




Midnight Bronze




Midnight Blue BV




Midnight Storm




Midnight Storm Beige




Midnight Blue Varnish



Midnight Aloe



Midnight Wheat




Storm Wheat Blue Varnish




Midnight Amber White



Pearl




Linen Wheat Smudge




White Pearl




Pearl Linen




Amber White



Linen



Linen White



Natural White



White

Product: EXTRAVIEW® Plus Sunscreens Colour: Midnight Storm

Note: Colours are as accurate as the printing process allows



green building council australia
MEMBER



HunterDouglasCommercial

WINDOW COVERINGS

EXTRAVIEW® Plus Sunscreen Fabric

features and benefits

PVC Coated Fibreglass

Sunscreens can let in natural light whilst reducing the level of glare, it is particularly good in situations where computer screens are used.

1 x 2 Basket Weave Design

Modern design which provides a consistent weave look.

20 Colours

Modern colour range designed to suit most Australian interiors.

Stable Fabric

Fibreglass does not stretch, shrink or twist.

Excellent Solar Optical Properties

The solar optical properties include heat protection, insulation, shade factor, glare reduction and UV protection.

Light Filtering

The unique weave allows light to filter through and provides a certain level of daytime privacy.

UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

Woven In Australia

Proudly woven in Australia to support the Local Textiles Industry.






VOCs

EXTRAVIEW® Plus Sunscreen Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11).

MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of EXTRAVIEW® Plus Sunscreen Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

Solar Optical Properties and COMFORT RATING Guide#

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	 Heat Protection	 Insulation	 Shade Factor	 Glare Reduction	 UV Protection
Midnight Storm Beige	7	12	81	9	9	82	6	0.69	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight Amber White	7	18	75	9	15	76	5	0.65	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight Smudge	6	6	88	8	5	87	5	0.73	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight Blue Varnish	6	8	86	8	6	86	6	0.71	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Storm Wheat Blue Varnish	7	20	73	8	15	77	5	0.63	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight	7	3	90	7	3	90	6	0.75	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight Aloe	6	13	81	8	8	84	5	0.68	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight Storm	7	7	86	8	6	86	6	0.72	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight Blue/Blue Varnish	7	10	83	9	6	85	6	0.70	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Amber White	22	58	20	15	39	46	6	0.41	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
Linen Wheat Smudge	12	37	51	12	28	60	6	0.53	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
Linen	20	51	29	13	36	51	6	0.45	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
Linen White	21	54	25	15	41	44	6	0.43	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
Pearl Linen	13	37	50	10	28	62	6	0.53	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
Pearl	10	30	60	9	23	68	6	0.57	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
White Pearl	15	46	39	12	35	53	6	0.47	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
White	24	61	15	18	46	36	6	0.39	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
Natural White	23	61	16	16	43	41	6	0.39	◆◆◆◆	◆◆	◆◆◆	◆◆◆	◆◆◆◆
Midnight Wheat	7	14	79	8	10	82	5	0.67	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆
Midnight Bronze	7	5	88	7	3	90	6	0.73	◆◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆◆

Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

COMFORT RATING Guide*

- uuuuu Highest level of protection/performance
- uuuu High level of protection/performance
- uuu Medium level of protection/performance
- uu Low level of protection/performance
- u No protection

COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

Fire Retardancy Information

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings. Not suitable for use in fire isolated exits of buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	5