

BLOCKOUT

SEYCHELLES FABRIC

Applications

Panel Glide
Roller Blinds
Roman Shades

Composition

100% Polyester

Weight

420gsm \pm 30gsm/m²

Fabric Thickness

0.65mm \pm 10mm

Roll Width

2.8m

Colour Fastness

6-7 Blue Scale

Stiffness


50mm \pm 10mm

6 Colours Available


Low VOCs

MULTIVISION® Concept


Australian Made



Empire




Drizzle



Champagne



Willow



Angora



Essence

Product: Seychelles Blockout Fabric Colour: Empire

Note: Colours are as accurate as the printing process allows



HunterDouglasCommercial

WINDOW COVERINGS

Seychelles Blockout Fabric

features and benefits

100% Polyester

6 Colours

A range of natural tones that have an incorporated tonal backing.

Textured Basecloth

Gives fabric a great look & feel as well as providing a durable easy clean surface.

UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

VOCs

Seychelles Blockout Fabric has been tested and does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11).

Sanitized® Antimicrobial Protection

Seychelles Fabric has been treated with Sanitized® Antimicrobial Protection which effectively reduces the development of bacteria, odour and mildew.

DURAGUARD® FABRIC PROTECTOR

Seychelles fabric has been treated with DURAGUARD® Fabric Protector which effectively repels most stain causing agents with its proven, water based, fluorochemical, formula. This fabric protection is totally invisible and has high levels of stain repellence. It makes cleaning and maintaining the fabric much easier.

MULTIVISION® Concept

MULTIVISION® is a group of fabrics that are perceived to be the same colour tone, but have different opacities. A number of Seychelles Blockout Fabric colours have been selected for the MULTIVISION® Concept. For more information refer to the Hunter Douglas Commercial MULTIVISION® Brochure.

Australian Made

Seychelles Fabric is proudly made in Australia to support the local textiles industry.

Solar Optical Properties and COMFORT RATING Guide#

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
Empire	0	7	93	0	6	94	0	0.70	◆◆◆◆◆	◆◆	◆◆◆◆◆	Blockout	◆◆◆◆◆
Willow	0	66	34	0	53	47	0	0.29	◆◆◆◆◆	◆◆	◆◆◆◆◆	Blockout	◆◆◆◆◆

Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

COMFORT RATING Guide#

- uuuuu Highest level of protection/performance
- uuuu High level of protection/performance
- uuu Medium level of protection/performance
- uu Low level of protection/performance
- u No protection

COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

Fire Retardancy Information

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings. Not suitable for use in fire isolated exits of buildings.

Ignitability Index [Range 0-20]	12	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	7

HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call 1300 733 078.

www.hunterdouglascommercial.com.au

© Copyright 2011. Hunter Douglas Limited (ABN 98 009 675 709). Sanitized® and the Sanitized® symbol are trademarks of SANITIZED AG, Switzerland, registered in numerous countries. *Registered Trade Marks of Hunter Douglas Limited. 01.11_VV/SEYCHELLES