

TRANSLUCENT

DUETTE® ARCHITELLA PANACHE FABRIC

Applications

DUETTE® Shades

Control Systems

Standard Cordlock

- Standard Bottom-up
- Top Down
- Top Down - Bottom-up
- Duo-lite

ULTRAGLIDE® Shades

- Standard Bottom-up
- Top Down
- Top Down - Bottom-up
- Duo-lite

PowerRise

EasyRise

Special Shapes

Motorisation

Composition

Wet-laid Polyester non woven as outer cell, laminated polyester as inner cell

Vane Size

20mm

Colour Fastness

6-7 Blue Scale

6 Colours Available

Product: DUETTE® Architella Shades in Panache Fabric Colour: Daisy White

Note: Overseas hardware shown



HunterDouglasCommercial

WINDOW COVERINGS

DUETTE® Architella Panache Translucent Fabric

features and benefits

Fabric Specifications

20mm pleats. Wet-laid polyester non woven as outer cell, laminated polyester as inner cell.

Energy Efficiency

DUETTE® Shades provide superior insulation and energy efficiency to regulate temperature and minimise heating and cooling loads.

Three Distinct Air Pockets

For superior energy efficiency; increased insulation.

TruPleat Construction

For a more uniform appearance.

Layers Of Fabric

For more intense colour.

Design Flexibility

DUETTE® Shades are available in a range of different sizes to suit commercial applications and can be manufactured to fit special window shapes.

Blockout

All colours in the range block light providing a high level of privacy factor.

6 Colours






A range of neutrals & great new season designer colours.

UV Resistant

99% UV blockage.

Solar Optical Properties and COMFORT RATING Guide*

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
Linen	18	68	14	14	49	37	0	0.32	◆◆◆◆◆	◆◆◆◆◆	◆◆◆◆◆	◆◆◆◆◆	◆◆◆◆◆

<p>Solar Optical Properties Guide</p> <p>Ts - Heat Transmittance (%) Rs - Heat Reflectance (%) As - Heat Absorbance (%) Tl - Light Transmittance (%) Rl - Light Reflectance (%) Al - Light Absorbance (%) Tuv - Ultraviolet Transmittance (%) Sc - Shading Coefficient</p>	<p>COMFORT RATING Guide*</p> <p>◆◆◆◆◆ Highest level of protection/performance ◆◆◆◆ High level of protection/performance ◆◆◆ Medium level of protection/performance ◆◆ Low level of protection/performance ◆ No protection</p> <p># COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.</p>	<p> Heat Protection</p> <p> Glare Reduction</p> <p> Shade Factor</p>	<p> Insulation</p> <p> UV Protection</p>
--	--	---	--

Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	0-1

HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call **1300 733 078**.

www.hunterdouglascommercial.com.au

© Copyright 2008. © Registered Trade Marks of Hunter Douglas Limited (ABN 98 009 675 709).
10.08_C7759/DUETTE® Architella Panache