

TRANSLUCENT SEMI BLOCKOUT

SILHOUETTE® BON SOIR FABRIC

Applications

SILHOUETTE® Shadings

Control Systems

Standard Cord Loop

EasyRise

Motorised Shadings

ULTRAGLIDE® Shadings

Composition

100% Spun Polyester

Vane Size

50mm

75mm

Colour Fastness

6-7 Blue Scale

8 Colours Available



Product: SILHOUETTE® Shadings in Bon Soir Semi Blockout Fabric Colour: Sleepy Beige



HunterDouglasCommercial

WINDOW COVERINGS

SILHOUETTE® Bon Soir Semi Blockout Fabric

features and benefits

Fabric Specifications

100% anti-static spun bonded polyester yarn.

Design Flexibility

The distinctive fabric vane suspended between two sheer facings provides the versatility of two products in one; with the vanes closed, the shade can be raised and lowered for complete privacy or complete view through.

Blockout

All colours in the range block light providing a high level of privacy factor.

8 Colours

A range of neutrals & great new season designer colours.

Solar Optical Properties and COMFORT RATING Guide#

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
Seclusion White*	0	61	39	1	53	46	<1	0.37	◆◆◆◆◆	◆◆	◆◆◆◆◆	◆◆◆◆◆	◆◆◆◆◆

*US test results

Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- Tl - Light Transmittance (%)
- Rl - Light Reflectance (%)
- Al - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

COMFORT RATING Guide#

- ◆◆◆◆◆ Highest level of protection/performance
- ◆◆◆◆ High level of protection/performance
- ◆◆◆ Medium level of protection/performance
- ◆◆ Low level of protection/performance
- ◆ No protection

COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings. Not suitable for use in fire isolated exits of buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	3

HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call **1300 733 078**.

www.hunterdouglascommercial.com.au

© Copyright 2008. © Registered Trade Marks of Hunter Douglas Limited (ABN 98 009 675 709).
10.08_C7759/SILHOUETTE® Bon Soir