

**TRANSLUCENT**

**SILHOUETTE® ORIGINALE  
FABRIC**

**Applications**

SILHOUETTE® Shadings

**Control Systems**

Standard Cord Loop

EasyRise

Motorised Shadings

ULTRAGLIDE® Shadings

**Composition**

100% Spun Polyester

**Vane Size**

50mm

75mm

**Colour Fastness**

6-7 Blue Scale

**20 Colours Available**



Product: SILHOUETTE® Shadings in Originale Fabric Colour: Blue Bell



**HunterDouglasCommercial**

WINDOW COVERINGS

# SILHOUETTE® Originale Translucent Fabric

## features and benefits

### Fabric Specifications

100% anti-static spun bonded polyester yarn.

### Design Flexibility

The distinctive fabric vane suspended between two sheer facings provides the versatility of two products in one; with the vanes closed, the shade can be raised and lowered for complete privacy or complete view through.

### Light Filtering

All colours in the range allow light to filter through the fabric providing a low-mid level of privacy factor.






### 20 Colours

A range of neutrals & great new season designer colours.

## Solar Optical Properties and COMFORT RATING Guide\*

COLOUR	Ts	Rs	As	Tl	Rl	Al	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
Originale White	0	62	38	0	54	46	<1	0.45	◆◆◆◆◆	◆◆	◆◆◆◆◆	◆◆◆◆◆	◆◆◆◆◆

<b>Solar Optical Properties Guide</b> Ts - Heat Transmittance (%) Rs - Heat Reflectance (%) As - Heat Absorbance (%) Tl - Light Transmittance (%) Rl - Light Reflectance (%) Al - Light Absorbance (%) Tuv - Ultraviolet Transmittance (%) Sc - Shading Coefficient	<b>COMFORT RATING Guide*</b> ◆◆◆◆◆ Highest level of protection/performance ◆◆◆◆ High level of protection/performance ◆◆◆ Medium level of protection/performance ◆◆ Low level of protection/performance ◆ No protection # COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.	 Heat Protection	 Insulation
		 Glare Reduction	 UV Protection
		 Shade Factor	

## Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings. Not suitable for use in fire isolated exits of buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	3

# HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call **1300 733 078**.

[www.hunterdouglascommercial.com.au](http://www.hunterdouglascommercial.com.au)

© Copyright 2008. © Registered Trade Marks of Hunter Douglas Limited (ABN 98 009 675 709). 10.08\_C7759/ SILHOUETTE® Originale