

TRANSLUCENT

20mm DUETTE® SYMPHONY FABRIC

Applications

DUETTE® Shades

Control Systems

Standard Cordlock

- Standard Bottom-up
- Top Down
- Top Down - Bottom-up
- Duo-lite

ULTRAGLIDE® Shades

- Standard Bottom-up
- Top Down
- Top Down - Bottom-up
- Duo-lite

PowerRise

EasyRise

Special Shapes

Motorisation

Composition

100% Spunbond Polyester
non woven

Vane Size

20mm

Colour Fastness

6-7 Blue Scale

15 Colours Available

Product: 20mm DUETTE® Shades in Symphony Fabric Colour: Mocha Parfait

Note: Overseas hardware shown



HunterDouglasCommercial

WINDOW COVERINGS

20mm DUETTE® Symphony Translucent Fabric

features and benefits

Fabric Specifications

20mm pleats. 100% anti-static spun bonded polyester yarn, light filtering, coloured face with white backing.

Energy Efficiency

DUETTE® Shades provide superior insulation and energy efficiency to regulate temperature and minimise heating and cooling loads.

Design Flexibility

DUETTE® Shades are available in a range of different sizes to suit commercial applications and can be manufactured to fit special window shapes.

Light Filtering

All colours in the range allow light to filter through the fabric providing a low-mid level of privacy factor.

15 Colours

A range of neutrals & great new season designer colours.

UV Resistant

99% UV blockage.

Solar Optical Properties and COMFORT RATING Guide#

COLOUR	Ts	Rs	As	TL	RL	AL	Tuv	Sc	Heat Protection	Insulation	Shade Factor	Glare Reduction	UV Protection
Daisy White*	28	59	13	21	44	35	<1	0.41	◆◆◆◆	◆◆◆◆◆◆	◆◆	◆◆	◆◆◆◆◆◆

*US test results

Solar Optical Properties Guide

- Ts - Heat Transmittance (%)
- Rs - Heat Reflectance (%)
- As - Heat Absorbance (%)
- TL - Light Transmittance (%)
- RL - Light Reflectance (%)
- AL - Light Absorbance (%)
- Tuv - Ultraviolet Transmittance (%)
- Sc - Shading Coefficient

COMFORT RATING Guide#

- ◆◆◆◆ Highest level of protection/performance
- ◆◆◆ High level of protection/performance
- ◆◆ Medium level of protection/performance
- ◆ Low level of protection/performance
- ◆ No protection

COMFORT RATING Guide has been devised by Hunter Douglas Limited with the assistance of Canesis Pty Ltd - an Independent Australian Fibre and Textile Research and Development Company.



Heat Protection



Insulation



Glare Reduction



UV Protection



Shade Factor

Fire Retardant

Complies with the General Requirements of the Building Code of Australia for Fire Hazard Properties of materials in buildings.

Ignitability Index [Range 0-20]	0	Heat Evolved Index [Range 0-10]	0
Spread of Flame Index [Range 0-10]	0	Smoke Developed Index [Range 0-10]	2

HunterDouglasCommercial

WINDOW COVERINGS

To see how Hunter Douglas Commercial Window Coverings can transform your next project call **1300 733 078**.

www.hunterdouglascommercial.com.au

© Copyright 2008. © Registered Trade Marks of Hunter Douglas Limited (ABN 98 009 675 709).
10.08_C7759/20mm DUETTE® Symphony